

DESIGN OF FLOOR BEAM

DESIGN PARAMETERS:-

| | | | | |
|-------------------------------------|-----|---|-------|-------------------|
| Characteristic strength of concrete | fc' | = | 38.00 | N/mm ² |
| Characteristic strength of steel | fy | = | 420 | N/mm ² |

STAAD PRO RESULTS:-

| | | | | |
|--|-------------------|---|--------|----------------------------|
| Maximum moments from both the beams are considered for design, | | | | Support moment at col.Face |
| Maximum bending moment @face of support | M _{sup} | = | 219.99 | kN-m Beam No. 58 L/C 102 |
| Maximum bending moment @mid span | M _{span} | = | 195.82 | kN-m Beam No. 12 L/C 102 |
| Maximum shear at 'd' distance from support face | V _{umax} | = | 291.24 | kN Beam No. 23 L/C 102 |
| Maximum Torsional Moment at Support | T _{umax} | = | 4.81 | kN.m Beam No. 60 L/C 102 |

A) DESIGN FOR BENDING:-

1) DESIGN OF REINFORCEMENTS FOR BENDING:-(AT SUPPORTS)

| | | | | | |
|--|-----|---|-----------------|----|-------------|
| Width of beam | b | = | 300 | mm | |
| Total depth of beam | D | = | 500 | | |
| Diameter of main reinforcement | dt | = | 20 | mm | at support |
| Diameter of main reinforcement | db | = | 20 | mm | at Mid span |
| Clear cover to the reinforcement | cc | = | 50 | mm | |
| Effective depth of beam for bottom steel | deb | = | (500 - 50 - 10) | | |
| | | = | 440 | mm | |
| Effective depth of beam for top steel | det | = | (500 - 50 - 10) | | |
| | | = | 440 | mm | |

I Main Reinforcement (Top Steel):-

| | | | | | |
|--------------------------------------|--------------------|--------|---|------------------|-------------------|
| Bending moment at supports | M _{sup} | = | 219.992 | kN-m | |
| Strength reduction factor | φ | = | 0.9 | | Cl. 9.3.1 ACI 318 |
| Moment resistance factor | Ru | = | M _{sup} /φ x b x det ² | | |
| | Ru | = | 219992000 / (0.9 x 300 X440 ²) | | |
| | | = | 4.210 | | |
| Steel reinforcement factor | m | = | 420/ (0.85 x 38) | | |
| | | = | 13.000 | | |
| Percentage of steel required | ρ _{reqd} | = | 1/m x(1- sqrt (1-(2Ru x m / fy)) | | |
| | | = | 1/13 x (1 - sqrt (1- (2 x 4.21 x 13/420))) | | |
| Required percentage of steel | ρ _{reqd} | = | 1.078 | % | |
| Minimum percentage of steel | ρ _{min} | = | 0.367 | % | Cl.10.5.1 ACI 318 |
| Governing percentage of steel | ρ _{Des} | = | 1.078 | % | |
| Minimum area of steel required | As _{des} | = | 0.01078 x 300 x 440 | | |
| | | = | 1422.96 | mm ² | |
| Number of bars required | Nos | = | 1422.96 / Pi() / 4 x 20 ² | | |
| | | = | 4.53 | | |
| Number and diameter of bar | 3 | Nos of | 20 | mm or equivalent | |
| | 3 | Nos of | 16 | mm or equivalent | |
| Area of steel provided | As _{prov} | = | 1545.66 | mm ² | |
| Provided percentage of reinforcement | ρ _{prov} | = | 1.030 | % | |
| Maximum percentage of reinforcement | ρ _{max} | = | 1.030 | % | |

Area of steel provided (As prov)> than (As des) Hence Safe

II Main Reinforcement (At mid span):-

| | | | | | |
|----------------------------|------------------|---|--|------|-------------------|
| Bending moment at supports | M _{sup} | = | 195.823 | kN-m | |
| Strength reduction factor | φ | = | 0.9 | | Cl. 9.3.2 ACI 318 |
| Moment resistance factor | Ru | = | M _{sup} /φ x b x det ² | | |
| | Ru | = | 195823000 / (0.9 x 300 X440 ²) | | |
| | | = | 3.750 | | |
| Steel reinforcement factor | m | = | 1.078/ (0.85 x 0.36692940493863) | | |
| | | = | 3.460 | | |

For Combined Shear & Torsion :

$$= 1.36745 \text{ mm}^2/\text{m}/ 2 \text{ Legs}$$

$$= At/s + Av/s$$

$$= 0.00022 + 1.37$$

$$= 1.36768 \text{ mm}^2/\text{m}/ 2 \text{ Legs}$$

Diameter of stirrups d_s 12 mm branches 2

Area of steel $A_s = 226.08 \text{ mm}^2$

Spacing required $S = 165.302 \text{ mm}$

$S \text{ Max1} = 150 \text{ mm}$

$S \text{ Max2} = -$

Use **12** mm Dia @ **150** mm c/c

CI.11.6.3.8
 ACI 318
 Cl. 11.4.5
 ACI 318

Check minimum Stirrups Area

minimum Stirrups Area $Av + 2 At = 0.062 \times \text{sqrt}(f'c) \times b \times S / f_{yt}$

$$= 40.95 \text{ mm}^2$$

but not less than $0.35 \times b \times S / f_y = 37.50 \text{ mm}^2$

Actual Stirrups Area Provided $= 753.6 \text{ mm}^2$

$= \text{Hence safe}$

Calculate longitudinal torsion reinforcement

Here $T_u < \phi_{cr}$

So No need to design for Tosion and longitudinal torsion reinf

Design Summary :

| | | | | | | | | | |
|--------------|-----------|-------|------------|-----|---|----------|-----|-----------|-----|
| Top Rebar | 3 | Nos | 20 | Dia | + | 3 | Nos | 16 | Dia |
| Bottom Rebar | 3 | Nos | 16 | Dia | + | 3 | Nos | 16 | Dia |
| Stirrups | 12 | Use @ | 150 | C/C | | | | | |

